

V 810 VA

Technical data

Internal chamber dimensions External dimensions

s 850 x 670 x 200 mm* 1070 x 1000 x 1980 mm**/ 2200 mm with lid open

810 mm

Seal length Vacuum pump Weight

Power supply

100 m³/h or 160 m³/h 400 kg or 470 kg

3 phases, 230 / 400 V, 50 Hz***

^{*}width x height x depth
**width x depth x height
special voltages upon request





Quantity and position of the welding bars according to individual agreement.



made in Germany

BOSS quality characteristics



Longevity

BOSS vacuum machines are made exclusively with high-quality individual components: rust-free stainless steel, splashproof elements and Busch high-performance pumps – 100% Made in Germany. Clear structure, robust technology and sophisticated design guarantee long-lasting operational readiness.



User-friendliness

Our intuitive Z 3000 sensor control unit permits simple and precise setting of important operating parameters. Pre-set values can be recalled via the memory function. The well-thought-out and ergonomic construction of the machines permits user-friendly working and guarantees optimum packaging results.



Seal welding

The perfect synergy of contact pressure, seal welding temperature and seal welding time produces optimum fusing results. Our seal welding systems are suitable for all commercially available vacuum bags. The bag overlap is cut off in order to avoid unnecessary bacterial exposure. The machine can be optionally equipped with double seam seal weld..



Service & Cleaning

Ease of cleaning is foremost in the design of our machines. They are made of stainless steel. The vacuum chambers are deep-drawn and the sealing systems cable-free. In order to reduce service costs and avoid downtimes due to maintenance, we attach great importance to easy accessibility and the clear arrangement of individual components. A service programme supports the functionality of the vacuum pump.







Lid and chamber

The stainless steel vacuum chamber is designed to be easy to clean. The lid is made of high-quality stainless steel and an inspection glass permits permanent process monitoring.

Chamber



Benefits

- Combination with roller tracks possible
- Cable-free pressure systems
- Smooth surfaces for easy cleaning
- Individual chamber depths / heights upon request
- Dust filter for powdery products (optional)

Shelves



Benefits

- Height adjustment by adjustable insertion plate (optional)
- Storage boxes with handles in various sizes
- Reduction of evacuation time due to volume-reducing insertion plates

Stainless steel lid



Benefits

- Space-saving lid guide thanks to vertical swing mechanism
- · Different dimensions upon request
- Cover fixing mechanism
- · Silicone lip seal for smooth lid closure
- Additional stability thanks to supporting struts
- Inspection glass in the lid (optional)





Control system


Control system Z 3000

Our Z 3000 sensor control is equipped with a precision vacuum sensor and permits precise setting of important operating parameters. Vacuum, gas and sealing.

PROG VAC GAS C Z3000 OFF WEBAX WEB W MA G C F SE SE SE SE No PRINTE SENS SECRET TO BE A SEASON SECRET TO SEASON SECRET TO

Benefits

- · User-friendliness
- 99-programme memory
- · Clear depiction of individual parameters
- Break function for immediate process cancellation
- H2O sensor for automatic packaging of liquid products flexibly adjustable according to customer requirements
- · Quick-stop function for packaging liquids
- Incremental vacuum function for slowly degassing products
- Cyclic vacuum permits multiple flushing of the bag
- Continuous running service programme for automatically cleaning the vacuum pump
- Separately controllable sealing systems
- Splashproof design
- Soft-air function for gentle back ventilation (optional)
- Individual setting of cooling, pressing on and back ventilation times
- Operating hours counter for monitoring service intervals



Seal welding

Double seal weld







Simple cut-off seal weld





Round wire: 1,2 mm Ø Flat wire: 4 x 0,2 mm



Separately adjustable cut-off seal weld





Round wire: 1,2 mm Ø Flat wire: 4 x 0,2 mm



Over-/ under seal weld





Flat wire above: 8 x 0,2 mm Flat wire below: 6 x 0,2 mm







BUSCH vacuum pump

Our BOSS vacuum packaging machines are fitted with powerful oil-driven rotary disc vacuum pumps made by the Busch Company.



Benefits

- Reduction of oxygen content by up to max. 0.1%
- Constant high vacuum level
- Optimum conservation of moisture-sensitive and/or oxygen-sensitive products
- Long-term replacement part guarantee
- · Service-friendly design
- Technically mature, long-life technology Made in Germany
- Gas ballast valve for the evacuation of larger quantities of steam

Technical data

Nominal pumping speed	100 m³/h	160 m³/h
Ultimate pressure (mBar)	0,1	0,1
Nominal motor rating (kW)*	~ 2,7	~ 4
Nominal motor speed (U/min)	1500	1500
Noise level (ISO 2151) (dB)	65	70
Oil capacity (liter)	2	5

^{*} depends on the voltage supply

Accessories

- 1. Gas flush device with 5 nozzles
- 2. Simple cut-off seal weld
- 3. Over-/ under seal weld (not possible in combination with separately adjustable cut-off seal)
- 4. Separately adjustable cut-off seal weld
- 5. Pump 160 m³/h, 3 phases; 230/400 V, 50 Hz
- 6. Slow air release
- 7. Inspection glass in the lid (maximally 2 glasses possible)
- 8. Automatic lid shift
- 9. Dust filter to protect vacuum pump
- 10. Bag support box (stainless steel)
- 11. Height-adjustable insertion plate including holder right/left
- 12. Automatic lifting table in front of the machine including roller track in the machine
- 13. Height adjustable roller track, 300 mm wide (stainless steel)
- 14. Set of wearing parts (teflon, wire, lid gasket, silicone for pressure bar)
- 15. Packaging (stable cardboard box on wooden pallet)



























